

COM RANGE

ROBUST IP65 BULKHEAD LUMINAIRE



Robust LED polycarbonate bulkhead luminaire sealed to IP65. Available in a white base with a clear polycarbonate Fresnel diffuser and a choice of 4 exit legends

It is available for normal mains lighting, and is also available with integral 3hr maintained emergency kit. For low ceiling heights the COM can be supplied with a semi-recessing kit.

LUMINAIRE CAT NO.	VERSION	NOMINAL SIZE MM	POWER tcW	LUMEN OUTPUT*	WEIGHT KG
COMLED/M	MAINTAINED	350 X 120	3.0	150	1.1
COMLED	MAINS	350 X 120	1.7	150	0.9

*Lumen output of the luminaire without sign legend

ADDITIONAL ORDERING INFORMATION

- Emergency self-test (M version only) - add /EMST
- DALI - add /DALI
- Self-adhesive legend - add /AL
- Suspended legend - add /SL
- Semi-recessing kit - add /SR

Body Colour:

- White as standard

FEATURES

- Polycarbonate construction
- IP65 rated
- Suspended legend version available on request
- Choice of 4 self-adhesive exit legends in either ISO or EC format
- Mains, maintained, DALI and Self-test versions
- Semi recessing kit available

LEGEND OPTIONS



LP 2

Door Arrow Left

LP 3

Door Arrow Right



LP 4

Door Arrow Up

LP 5

Door Arrow Down

DIMENSIONS

