

FGB(IP) RANGE

IP65 IK08 LED BATTEN



The FGB(IP) range is a sturdy and effective IP65 surface mounted batten fitting for more challenging applications. It is manufactured from robust aluminium with a polycarbonate diffuser giving the fitting an IK10 impact rating. The FGB(IP) is available in a choice of 3 lengths – 600mm, 1200mm and 1500mm long. This high specification luminaire has been designed for a life expectancy of 50,000 hours, CRI Ra>80 with the option of adding an integral 3hr emergency kit.

LUMINAIRE CAT NO	NOMINAL SIZE MM	LUMEN OUTPUT*	POWER (tcW)	WEIGHT KG	DIM OPT	EM OPT
FGB(IP)201	600	2,600	22	1.6	-	•
FGB(IP)401	1,200	4,625	40	2.0	-	•
FGB(IP)501	1,500	6,850	60	2.4	-	•

*The lumen output of the luminaire

ADDITIONAL ORDERING INFORMATION

- Emergency version - add /EM
- Body Colours:
 - Grey as standard
 - LED Colours:
 - Cool White (4,000k) - add /CLCW

FEATURES

- Lifetime of 50,000 hours
- IP65 rated
- IK08 impact rating
- CRI >80
- Surface mounted as standard.
- White Powder coated aluminium frame
- Up to 118 Llm/tcW

DIMENSIONS

