

LCM-SLIM RANGE

SLIMLINE LED SURFACE OR SUSPENDED MODULAR / CONTINUOUS SYSTEM



The LCM(SLIM) is a thinner version of our popular LCM being only 40mm wide and is manufactured from high grade extruded aluminium in modular – 600, 850, 1250 & 1550 lengths or as a continuous length / geometric arrangement. It comes as standard with a flat panel opal PMMA diffuser. A low glare Micro Prism diffuser is also available.

The LCM(SLIM) can be supplied with DALI dimmable drivers (DSI dimming versions are also available) with integral emergency options, and the choice of being either surface mounted or suspended (wire suspensions as standard although rods are available). Combined with the choice of lengths and output options, this flexibility makes the LCM ideal for reception areas, offices, retail, and public buildings.

All versions come supplied as white (RAL9010) as standard with the option to finish in any other RAL colour on request.

LUMINAIRE CAT NO.	NOMINAL SIZE MM	LUMEN OUTPUT*	POWER (tcW)	WEIGHT KGS	DIM OPT	EM OPT
LCM-SLIM/060(HE)	592	978	9.6	1.3	•	•
LCM-SLIM/060	592	1,407	14.7	1.3	•	•
LCM-SLIM/060(HO)	592	1,868	19.6	1.3	•	•
LCM-SLIM/090(HE)	872	1,467	14.4	1.8	•	•
LCM-SLIM/090	872	2,112	22.1	1.8	•	•
LCM-SLIM/090(HO)	872	2,802	29.4	1.8	•	•
LCM-SLIM/120(HE)	1,152	1,956	19.2	2.5	•	•
LCM-SLIM/120	1,152	2,815	29.4	2.5	•	•
LCM-SLIM/120(HO)	1,153	3,736	39.1	2.5	•	•
LCM-SLIM/150(HE)	1,432	2,445	24.0	3.0	•	•
LCM-SLIM/150	1,432	3,519	36.8	3.0	•	•
LCM-SLIM/150(HO)	1,432	4,670	48.9	3.0	•	•
LCM-SLIM(CON)	**	2,344	24.5	2.0	•	•

*The lumen output of the luminaire based on 4,000K LED diodes with opal diffuser

** Typical values / meter

ADDITIONAL ORDERING INFORMATION

- | | | | |
|----------------------|----------------|---------------------|---------------|
| • DALI Dimming | - add /DALI | LED Colours; | |
| • DSI Dimming | - add /DSI | Warm white (3,000k) | - add /CLWW |
| • Emergency version | - add /EM | Cool white (4,000k) | - add /CLCW |
| • DALI Emergency | - add /DALI-EM | Body Colours: | |
| • Surface Mounted | - add /SUR | White (RAL 9010) | - as standard |
| • Wire Suspension | - add /DSW | Black | - add /B |
| • Opal diffuser | - add /OP | Silver Grey | - add /SG |
| • Prismatic diffuser | - add /PP | | |

FEATURES

- Slim 40mm wide body
- Opal PMMA flat panel diffuser as standard.
- Low glare micro-prismatic diffusers also available.
- Integral emergency and self-test conversions.
- DALI Dimming and DSI dimming available
- CRI 80 – CRI 90 available on request
- 3,000k or 4,000k colour option – tuneable white available on request.
- Surface or suspended options.
- Modular, continuous or geometric arrangements available.
- White (RAL9010) as standard - other RAL colours available on request

DIMENSIONS

