

SDL(CVE) RANGE

SMALL DIAMETER DOWNLIGHT WITH CURVED BEZEL



The SDL(CVE) has the same look as our larger LDL(CVE) fitting but, it only has a 51mm wide bezel. This makes for a very discrete fitting with the smooth radius bezel and set back lens giving a soft and subtle lighting effect on the bezel.

As with the rest of this family of fittings, the SDL(CVE)Ra98 comes as standard with a CRI of 98 with the R9 (red) spectrum value of 98, giving unbeatable colour rendering of near daylight quality

The fitting is sealed to IP54 as standard with the option to upgrade to IP65.

LED's are run via one driver which can be up to 20m from the luminaire making installation simple. Control options available: DALI, 1-10v, mains dimming and non-dimming with maintained or non-maintained emergency packs.

LUMINAIRE CAT NO	BEAM ANGLE	COLOUR TEMP(K)	POWER TcW	LUMEN OUTPUT*	EM OPT	DIM OPT
SDL(CVE)/Ra98	32°/42°	2700/3000	5.3	296	•	•

* Lumen output of the luminaire based on 3,000k LED diodes at 42° beam angle

ADDITIONAL ORDERING INFORMATION

- | | | |
|---------------------|--------------|---|
| • Mains dimming | - add /MDIM | LED Colours: |
| • 1-10v dimming | - add /110-D | • Very warm white (2700k) - add /CLVWW |
| • DALI dimming | - add /DALI | • Warm white (3,000k) - add /CLWW |
| • DMX compatible | - add /DMX | |
| • Emergency version | - add /EM | Bezel Finishes: |
| • Honeycomb louvre | - add /HC | • Textured white(RAL9010 70% Matt) - standard |
| • 32° beam angle | - add /NW | • Black (RAL9005) - add /B |
| • 42° beam angle | - add /MD | • Other RAL Colours - on request |
| • IP65 rating | - add /IP65 | • Metallic finishes - on request |

FEATURES

- Up to 61 Lm/tcW
- Up to L90 B5 at 50,000 hours
- Exceptional colour consistency, 2 Macadam Ellipse
- Up to CRI-98, R9-98 for exceptional colour rendering
- DALI, 1-10V, Main dimming (leading & trailing edge) & DMX compatible
- Emergency versions
- IP54 as standard, IP65 version also available
- RAL or metallic bezel finishes available on request

DIMENSIONS

