

VNS(SP) RANGE

SCREEN PRINTED FLAT PANEL LED MODULAR



The VNS(SP) flat panel LED modular is a backlit variant of our popular VNS fitting with the addition of a screen-printed image on the front face. There are a wide range of images that can be used on individual panels or split across multiple panels if required. The luminaire comes as standard with a TPb UGR<19 diffuser. There is a choice of colour temperatures or a tuneable white version with a variety of outputs to suit most applications.

The VNS(SP) can be supplied to fit either an exposed T- grid or plasterboard ceiling (using a plasterboard frame) or for additional effect can be supplied with a recessing frame to replicate a skylight. The skylight frame can be made to fit most ceiling types. As an emergency unit it can be supplied with an inverter to power the board or via a separate remote LED head.

These options mean it is perfectly suited as a low energy luminaire for a visually comfortable working environment, ideal for offices, schools, hospitals, banks, and public buildings.

LUMINAIRE CAT NO	NOMINAL SIZE MM	LUMEN OUTPUT*	POWER (tcW)	WEIGHT KG	DIM OPT	EM OPT
VNS(SP)60/HE	595x595	2,056	22	2.5	•	•
VNS(SP)60	595x595	2,880	30	2.5	•	•
VNS(SP)126	595x1,195	5,600	54	7.8	•	•
VNS(SP)1212	1,195x1,195	11,360	108	8.2	•	•

* Lumen output of the luminaire based on 4,000K diodes at 25°C ambient. Output will vary depending on the choice of screen-printed image

ADDITIONAL ORDERING INFORMATION

- DALI dimming - add /DALI
- Recessed Tee ceiling - add /R
- Plasterboard ceiling - add /PB
- Skylight Frame - add /SF
- Emergency version - add /EM

LED Colours:

- Warm white (3,000k) - add /CLWW
- Cool white (4,000k) - add /CLCW
- Daylight white (6,500k) - add /CLDW
- Tuneable white - add /TW

- Body Colours:
- White as standard

FEATURES

- Wide range of image available for screen printing
- CRI 80
- 3,000K, 4,000K and 6,500K colour temperature options
- Tuneable white version (2,700k – 6,500k) available with either DALI or manual control via a switch
- UGR<19 TPb diffuser as standard
- DALI dimming available
- Supplied to fit either an exposed tee or plasterboard ceiling, or with a skylight frame
- White powder coated aluminium frame
- Emergency with 3W LED remote head, or integral versions.
- IP20 as standard
- Up to 105 Llm/tcW

DIMENSIONS

