

WLL RANGE

SLIMLINE UPLIGHTER WITH GLASS DIFFUSER



Our WLL range is our wall mounted uplighter with unique design features for illuminating both the ceiling and walls. There is the option to provide a proportion of downward light through the punched slots with an additional LED board (fittings with UD suffix). The WLL meets the LG7/ LG4 requirements and is an ideal uplighter to supplement the main light source.

This luminaire comes with a clear or frosted glass diffuser as standard to limit dust infiltration and reduce glare. It is supplied with Osram ('PrevaLED') LED boards and can be ordered with either fixed output or DALI dimmable control gear.

Emergency versions can be supplied in the larger version with an integral inverter and an LED head mounted internally at one end of the luminaire. The LED head can be supplied with either a 60° or 110° beam angle.

LUMINAIRE CAT NO	NOMINAL LENGTH MM	LUMEN OUTPUT*	POWER (tcW)	WEIGHT KG	DIM OPT	EM OPT
WLL211	235 x 360	1,911	17.3	2.3	•	-
WLL220(HO)	235 x 360	3,004	27.2	2.3	•	-
WLL222	235 x 640	3,298	28.3	3.4	•	•
WLL222(UD)	235 x 640	3,016/754**	32.4	3.4	•	•
WLL240(HO)	235 x 640	5,753	52	3.4	•	•
WLL240(UD)	235 x 640	4,602/1,150**	52	3.4	•	•

HO indicates High Output

*The lumen output of the luminaire based on 4,000K LED diodes & frosted glass @25°C ambient

**Upward/downward light output

ADDITIONAL ORDERING INFORMATION

- DALI dimming - add /DALI
- EM integral LED 60° - add /EMLED/60°
- EM integral LED 110° - add /EMLED/110°
- Clear Diffuser - add /CL
- Frosted diffuser - add /FR
- Square front - add /SF

LED Colours:

- Warm White (3000k) - add /CLWW
- Cool White (4000k) - add /CLCW
- Daylight White (6,500k) - add /CLDW

Body Colours
 • White as standard
 • Other RAL colours available on request

FEATURES

- Incorporates energy efficient OSRAM light modules
- CRI 85
- 50,000 Hours L80/B10
- 3,000k/4,000k/6,500k colour options
- Supplied with fixed output driver as standard
- DALI dimming option
- Emergency integral 3W LED version available in the larger version
- Downward light option for the larger version
- Square fronted version also available on request
- Other RAL colours available on request
- Clear or frosted diffuser
- SELV
- Up to 126 Llm/tcW
- Modular construction allows for end-of-life upgrade of boards and gear

DIMENSIONS

